

Gasdruckregelgerät Typ RR 100

Vorstufen



Führungsbereich (bar)	Feder	Draht ϕ mm
0,4 – 3	955-201-68	6
1 – 6	955-201-69	7
4 – 13	955-201-70	8,5



Führungsbereich (bar)	Feder	Draht ϕ mm
2 – 13	955-201-68	6
11 – 30	955-201-69	7
15 – 40	955-201-70	8,5
25-65	955-202-84	10

Regler



Führungsbereich (bar)	Feder	Draht ϕ mm
0,01 – 0,15	955-201-65	3,2



Führungsbereich (bar)	Feder	Draht ϕ mm
0,1 – 0,5	955-201-66	4
0,5 – 2	955-201-68	6
1 – 6	955-201-69	7
4 – 12	955-201-70	8,5

Einschub mit Kennzeichnung



Einschubvarianten

Typ	Düsen ϕ Show A	Feder- bezeich- nung	dicht E6 bar
Vorstufe MD/HD	1,5/98	VD 180-C	100
Plot MD	3/90	VD 130	18
Plot MD/HD	3/98	VD 203	80



Führungsbereich (bar)	Feder	Draht ϕ mm
6 – 30	955-201-69	7
15 – 40	955-201-70	8,5
25-65	955-202-84	10