


# ANDERSON GREENWOOD AMAL ERQ/ERQS FLAME ARRESTERS

End-of-line deflagration flame arresters designed to prevent the propagation of a flame.



#### **FEATURES**

- Fabricated construction.
- Replaceable element.
- Advanced crimped stainless steel element construction as standard. Other materials available.
- Independently tested and certified.
- Manufactured to ISO 9001:2015.

## **GENERAL APPLICATION**

The Types ERQ and ERQS are end-of-line flame arresters which are mounted on tanks or on the end of discharge pipes to stop flames entering the process. They allow short burning only.

## **TECHNICAL DATA**

Materials:
Carbon steel,
stainless steel

Sizes:
DN 15 to 600 [½" to 24"]

Connections:
Threaded or flanged

Temperature range:
-20 to 60°C [-4 to 140°F][1]

Gas groups:
IIA, IIB1, IIB2, IIB3, IIB, IIC

Certification:
ATEX Directive 2014/34/EU

<sup>1.</sup> Higher temperatures for certain gas groups.

# ANDERSON GREENWOOD AMAL ERQ/ERQS FLAME ARRESTERS

MATERIALS AND CONNECTION OPTIONS	Gas groups
	• IIA
Materials	• IIB1
Carbon steel and stainless steel.	• IIB2
	• IIB3
Connection pipe size	• IIB
Threaded DN 15 to 50 (1/2" to 2")	• IIC
Flanged DN 15 to 600 (1/2" to 24")	


#### NOTE

Accessories, special materials and connections are available on request.

## HIGH TEMPERATURE (+200°C (+392°F)) APPLICATIONS

Explosion group	Gap width	Inlet size							
IIB1 (IIA)	0.8 mm (0.032")	DN 15 to 600 (1/2" to 24")							
IIB	0.45 mm (0.018")	DN 15 to 600 (½" to 24")							
IIB2, IIB3	0.6 mm (0.024")	DN 15 to 300 (1/2" to 12")							
IIC	0.3 mm (0.012")	DN 15 to 300 (½" to 12" )							

## TYPE ERQ (EC VERSION)



### SELECTION GUIDE

SELI	ECTION GUIDE								
Exa	mple:	ERQ	50	EC	100	19	80	<b>S</b> 3	<b>S</b> 3
Mod	el								
ERQ									
ERQ	_								
	nection diameter								
	eaded								
	15 to 50 (½" to 2")								
Flar	•								
	15 to 600 (½" to 24")								
	nent code								
EC									
	nent diameter								
DN 50 to 100 (2" to 4") - threaded connection									
DN 50 to 800 (1" to 32") - flanged connection  Element width									
19	19 mm (0.75")								
	height								
80	0.80 mm (0.032")	45	0.45 mm (I	n n18")					
60	0.60 mm (0.024")		0.45 mm (l						
	nent material	10	0.10 111111 (	0.000 )					
53	Stainless steel								
С	Carbon steel								
Body material									
S3	Stainless steel								
С	Carbon steel								
53	Stainless steel								

### NOTES

All sizing and selection must be conducted by the factory. Standard elements are double the pipe size.